



45kW HMMWW Towable Trailer

Wheels Interchangeable with HMMWW • Front Fuel Filler and Gauge in Containment Box • Fuel Select Switch (Tank or Auxiliary) • Quick Connect Auxiliary Fuel Fittings for External Fuel Source • Engine Fluid Drains Ported to Frame • Automatic Shutdowns (Low Oil Pressure, High Coolant Temperature, Overspeed, Overcrank) • 15 1/2" Minimum Ground Clearance

OPTIONS: Composite Run Flats • Fuel Fired Coolant Heater Starts at 40 Below Without External Source of Power • Third Wheel at Tongue (rotates vertical for ramp crest) • Dual Wall Fuel Tank

Specifications:

Engine	4 cylinder turbo charged diesel
Generator Output	120/208 VAC 3-Phase 60-Hz; Rated 45kW at 10,000 ft. & 50°C
GVWR	5,500 lbs.
System Weight	3,900 lbs.
Fuel Capacity	40-Gallons Diesel DL-1, DL-2, JP-5 & JP-8 Fuel tank designed to maintain trailer wt & tongue wt ratio as fuel is added
Dimensions	85"W x 85"H x 148"L
Mobility	Designed for roll-on/roll-off C-130, C-141, C-5 & C-17. HMMWW towable.
Operating Environment	-40°F to 125°F (Fuel-fired coolant heater)
Noise	Less than 70 db at 25 ft.



860 Douglas Way • P.O. Box 530
Natural Bridge Station • VA 24579
(540) 291-4501 • Fax (540) 291-4502
www.powersystems-intl.com

Generator Trailer